

IS、IR 型清水泵性能参数表

型 号	流量	扬程	转速	电机功率	进出口径	
	(m <sup>3</sup> /h)	(m)	(r/min)	(kw)	吸入 (mm)	排出 (mm)
IS50-32-125	12.5	20	2900	2.2	50	32
	6.3	5	1450	0.55	50	32
IS50-32-160	12.5	32	2900	3	50	32
	6.3	8	1450	0.55	50	32
IS50-32-200	12.5	50	2900	0.5	50	32
	6.3	12.5	1450	0.75	50	32
IS50-32-250	12.5	80	2900	11	50	32
	6.3	20	1450	1.5	50	32
IS65-50-125	25	20	2900	3	65	50
	12.5	5	1450	0.55	65	50
IS65-50-160	25	32	2900	5.5	65	50
	12.5	8	1450	0.75	65	50
IS65-40-200	25	50	2900	7.5	65	40
	12.5	12.5	1450	1.1	65	40
IS65-40-250	25	80	2900	15	65	40
	12.5	20	1450	2.2	65	40
IS65-40-315	25	125	2900	30	65	40
	12.5	32	1450	4	65	40
IS80-65-125	50	20	2900	5.5	80	65
	25	5	1450	0.75	80	65
IS80-65-160	50	32	2900	7.5	80	65
	25	8	1450	1.5	80	65
IS80-50-200	50	50	2900	15	80	50
	25	12.5	1450	2.2	80	50
IS80-50-250	50	80	2900	22	80	50
	25	20	1450	3	80	50
IS80-50-315	50	125	2900	37	80	50
	25	32	1450	5.5	80	50
IS100-80-125	100	20	2900	11	100	80
	50	5	1450	1.5	100	80
IS100-80-160	100	32	2900	15	100	80
	50	8	1450	2.2	100	80

IS100-65-200	100	50	2900	22	100	65
	50	12.5	1450	4	100	65
IS100-65-250	100	80	2900	37	100	65
	50	20	1450	5.5	100	65
IS100-65-315	100	125	2900	75	100	65
	50	32	1450	11	100	65
IS125-100-200	200	50	2900	45	125	100
	100	12.5	1450	7.5	125	100
IS125-100-250	200	80	2900	75	125	100
	100	20	1450	11	125	100
IS125-100-315	200	125	2900	110	125	100
	100	32	1450	15	125	100
IS125-100-400	100	50	1450	30	125	100
IS150-125-250	200	20	1450	18.5	150	125
IS150-125-315	200	32	1450	30	150	125
IS150-125-400	200	50	1450	45	150	125
IS200-150-250	400	20	1450	37	200	150
IS200-150-315	400	32	1450	55	200	150
IS200-150-400	400	50	1450	90	200	150