

CQG 型不锈钢立式管道磁力泵性能参数表

型号	流量	扬程	效率	电机功率	汽蚀余量
	(m ³ /h)	(m)	(%)	(kw)	(m)
CQG25-110	4.0	15	27	0.75	2.3
CQG25-125	4.0	20	21	1.1	2.3
CQG25-160	4.0	32	17	2.2	2.3
CQG32-100	4.5	12.5	29	0.75	2.0
CQG32-125	4.5	20	29	1.1	2.3
CQG32-160	4.5	32	29	2.2	2.3
CQG32-200	4.5	50	17	4	2.0
CQG40-125	6.3	20	31	1.5	2.3
CQG40-160	6.3	32	25	3	2.3
CQG40-200	6.3	50	18	5.5	2.3
CQG40-250	6.3	80	13	11	2.3
CQG50-100	12.5	12.5	47	1.5	2.3
CQG50-125	12.5	20	43	2.2	2.3
CQG50-160	12.5	32	37	4	2.3
CQG50-200	12.5	50	31	7.5	2.3
CQG50-250	12.5	80	23	15	2.3
CQG65-100	25	12.5	54	2.2	2.5
CQG65-125	25	20	53	3	2.5
CQG65-160	25	32	48	5.5	2.5
CQG65-200	25	50	43	11	2.5
CQG65-250	25	80	35	18.5	2.5
CQG80-100	50	12.5	58	4	3.0
CQG80-125	50	20	57.5	7.5	3.0
CQG80-160	50	32	56	11	3.0
CQG80-200	50	50	52	18.5	3.0
CQG80-250	50	80	44	30	3.0
CQG100-100	100	12.5	61	7.5	4.5
CQG100-125	100	20	61	15	4.5
CQG100-160	100	32	61	18.5	4.5
CQG100-200	100	50	59	30	4.0
CQG100-250	100	80	54	45	4.0
CQG125-125	160	20	65	18.5	4.0
CQG125-160	160	32	63	30	4.0
CQG125-200	160	50	62	45	5.5
CQG125-250	160	80	60	75	5.0